



Ecosys®
FS-C8520MFP / FS-C8525MFP
 Color Multifunctionals for A3 Format

FS-6525MFP / FS-6530MFP
 Monochrome Multifunctionals for A3 Format



Color MFP
 FS-C8520MFP / FS-C8525MFP

Monochrome MFP
 FS-6525MFP / FS-6530MFP

New Design, New Definition
 Low-Cost, Professional Document Output in your Compact Office

- Easy to **OWN**
- Easy to **USE**
- Easy to **CONTROL**
- Easy to **SERVICE**
- Easy on the **ENVIRONMENT**



Powered by **HyPAS™**





	Color Series		Monochrome Series	
Model Name	FS-C8520MFP	FS-C8525MFP	FS-6525MFP	FS-6530MFP
Main Specifications				
Writing Method	Semiconductor laser			
CPU	PowerPC464 800MHz			
Print Speed (A4/Letter)	Simplex	20/20 ppm (Color/Mono)	25/25 ppm (Color/Mono)	25 ppm
	Duplex	16/16 ppm (Color/Mono)	20/20 ppm (Color/Mono)	25 ppm
First Print Time	11.0 sec. or less in Mono 14.0 sec. or less in Color	10.0 sec. or less in Mono 12.0 sec. or less in Color	8.0 sec. or less	
Warm up time	Recovery from sleep 23 seconds or less		Recovery from sleep 20 seconds or less	
Resolution	600 dpi		Fast 1200/600 dpi	
Control Panel	4.3" Color Touch Panel			
PDL	PRESCRIBE			
Main Memory	1.5GB Standard (Max. 2.0GB)		1.0GB Standard (Max. 2GB)	
Interfaces	1000BASE-T / 100BASE-TX / 10-BASE-T, USB Host, USB 2.0			
Paper Weight	Standard Tray: 60 to 256 g/m ² ; MP Tray: 60 to 256g/m ²		Standard Tray: 60 to 163 g/m ² ; MP Tray: 45 to 256 g/m ²	
Paper Capacity	Standard	1 x 500 sheets + 100 sheets (MP Tray)		
Paper Size	Cassette: A3 to A5R ; MPT: A3 to A6R			
Media Types	Plain; Rough; Vellum; Recycled; Preprinted; Bond; Color; Pre-punched; Letter Head; Thick; High Quality; Custom 1-8 (MP Tray: Transparency; Labels; Cardstock; Envelop; Coated)		Plain; Rough; Vellum; Recycled; Preprinted; Bond; Color; Pre-punched; Letter Head; Thick; High Quality; Custom 1-8 (MP Tray: Transparency; Cardstock; Envelop)	
External Dimensions (W x D x H)	590mm x 590mm x 748mm		590mm x 590mm x 694mm	
Weight	80kg		52.2kg	
Toner Capacity	[K] 12,000 pages; [C/M/Y] 6,000 pages ISO19798		15,000 pages ISO19752	
PM Cycle	200,000		300,000	
Supported Protocol	TCP/IP (IPv4/IPv6); NetBEUI; LPD; RAW; SMTP; POP3; FTP; SMB; LDAP; SNMP (v1/v3); HTTP(S); IPP; IPP over WSD (Print/Scan)			
Printer Specifications [Standard]				
Supported OS (Driver & Software)	KX Driver, KX(XPS) Driver, PCL/KPDL/XPS Mini Driver, Status Monitor, KYOCERA NET Admin, KYOCERA NET Viewer, KYOCERA Net Direct Print; Windows XP, Server2003/2008, Vista, 7 KPrint: Windows XP, Server2003 Quick Setup: Windows XP, Vista, Server2003/2008 PPD Driver: MAC OS X Version 10.2 or higher			
Duplex Print Function	Standard			
Printing Emulations	PCL6(5e, XL), KPDL3(PostScript3 Equivalent), XPS			
Scan Specifications [Standard]				
Scan Mode	Color			
Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 200 x 100 dpi, 200 x 400 dpi			
File Format	PDF/JPEG/TIFF/XPS			
Continuous Scan Speed	Mono	40 ipm (300/200 dpi), 20 ipm (600/400 dpi)		40 ipm (300/200 dpi), 20 ipm (600/400 dpi)
	Color	40 ipm (300/200 dpi), 20 ipm (600/400 dpi)		20 ipm (300/200 dpi), 10 ipm (600/400 dpi)
Transmission Type	Scan to Email; Scan to FTP; Scan to SMB; WSD Scan; USB Memory			
Copy Specifications [Standard]				
Resolution	600 x 600 dpi			
Continuous Copy Speed (A4/ Letter)	Color / Mono: 20cpm	Color / Mono: 25cpm	25cpm	30cpm
First Copy Speed	11.7 sec or less in Mono 13.6 sec. or less in Color		7.8 sec or less	
Fax Specifications - Fax, Network Fax Function [Optional]				
Transmission Mode	Super G3			
Data Compression	MH/MR/MMR/JBIG			
One Touch Dial	100 entries			
Address Book	200 entries			
Modem Speed	33.6 kbps			
No. of line	Single			
Standard Option				
Document Processor	Paper Weight	Simplex 45-160 g/m ² ; Duplex 50-120 g/m ²		
	Feeder Capacity	50 sheets or less (50-80 g/m ²)		
	Paper Size	A3 [11" x 17"]		
Duplex	Embedded			
Job Separator	Standard			
Consumables & Maintenance Kit				
Toner Cartridge	[K] TK-899 K, [Y/M/C] TK-899 Y/M/C		TK-479	
Maintenance Kit	MK-895 A, MK-895 B, MK-470		MK-479, MK-470	
Additional Options				
Finisher	DF-470 + AK-470 (Hanger type 500 sheets Staple Finisher) Paper Weight: 52-256 g/m ² ; Staple weight: Less than 90 g/m ² ; Staple Position [1 staple: front/rear, 2 staples: center]			
Paper Feeder (Cassette)	PF-470 (500 sheets)			
FAX Kit	FAX System [U]			
IC Card Reader Kit	Card Authentication Kit (B) / (B) AC			
Gigabit Ethernet	IB-50			
USB Keyboard	Optional			

Disclaimer: Specifications and external appearances are subject to change without prior notice. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

KYOCERA
Kyocera Document Solutions India Pvt. Ltd.
 Second Floor, Centrum Plaza, Golf Course Road,
 Sector-53, Gurgaon, Haryana 122 002, India
 Phone: +91-0124-4671081
 Fax: +91-0124-4671001
 http://www.kyoceradocumentsolutions.co.in
 Email: bimal.nanda@did.kyocera.com

© All rights reserved. Brochure/KDAS/201205/Smart MFP HyPAS

KYOCERA Business Partner

KYOCERA
 Document Solutions